




GRAPHITE HYBRID SHEET / GHS-25



Stacked layers work together to prevent hot spots and returned heat to the device.

- Ideal for attaching to the inside of plastic case of electronic devices.
- Low thermal conductivity layer reduces speed of heat transfer to graphite layer, prevents hot spots from occurring, and impedes heat reflection back to the heat source.
- One side heat-resistant adhesive tape.
- Addition of low heat reflection layer helps to reduce the temperature of heat source.


Specifications

(The values below are not guaranteed.)


Property	Unit	Measurement method	GHS-25
Thickness	mm	—	0.6
Thermal Conductivity (Thickness direction*1 : whole product)	W/m·K	Hot wire method	3.0±1.0
Thermal Conductivity (Surface direction*1 : graphite layer only)	W/m·K	Laser flash method	≥1,400
Operating Temperature	°C	—	-40 ~ 150

*1: Please refer to Figure 1 on the right for the thermal conductivity measurement direction


● Figure 1: Thermal Conductivity Measurement Direction




Cross-section view



Application Example



Performance comparison



	Heating element temperature	Plastic board temperature
No countermeasures	90.5	48.2
Graphite sheet only	103.7(+13.2)	39.6(-8.6)
GHS-25	83.6(-6.9)	35.9(-12.3)

Unit: °C

- The specifications are for reference only, and not a guarantee. Information may change without notice.
- Any reprinting or copying of content in this document is prohibited without our prior consent.